

Master Link Assemblies

Master link assemblies are used for 1, 2, 3 and 4-leg slings.



Certification

At no extra charge, this product can be supplied with a works certificate and/or EC Declaration. Test certificates can be supplied upon request.

Material:
Grade 8, alloy steel

Safety Factor:
MBL equals 4 x WLL

Finish:
Generally to EN 1677-4

Specifications

Working Load Limit (tons)	Diameter Bow (mm)	Diameter Pin (mm)	Diameter Eye (mm)	Width Eye (mm)	Width Inside (mm)	Length Inside (mm)	Length (mm)	Length Bolt (mm)	Thickness Nut (mm)	Weight Each (kg)
2.0	13.5	16	34	13.5	22	43	85	83	13	0.39
3.25	16.0	19	40	16.0	27	51	105	99	17	0.67
4.75	19.0	22	47	19.0	31	59	125	115	20	1.08
6.5	22.0	25	53	22.0	36	73	144	131	23	1.66
8.5	25.0	28	60	25.0	43	85	161	151	25	2.46
9.5	28.0	32	67	28.0	47	90	179	167	28	3.4
12.0	32.0	35	74	32.0	51	94	199	179	31	4.51
13.5	35.0	38	80	35.0	57	115	220	198	34	6.1
17.0	38.0	42	89	38.0	60	127	239	202	19	7.63
25.0	45.0	50	104	45.0	74	149	283	244	24	13.25
35.0	50.0	57	111	50.0	83	171	333	270	27	18.53
42.5	57.0	65	134	57.0	95	190	360	302	30	25.94
55.0	65.0	70	145	65.0	105	203	399	330	33	35.33
85.0	75.0	83	163	75.0	127	229	455	376	40	52.97

* From 60 t without flat part